



| | | | | | | | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|------|----|-----|-----|----|----|----|----|-------|-------|
|  Lesnické pletivo ECONOMY  | povrchová úprava / vlastnosti pozinkované žárový Zn | 1000 | 15 | 2,0 | 1,6 | 8 | 15 | 50 | bm | 18,75 | 22,69 |
| | | 1200 | | | | 10 | 18 | | | 21,13 | 25,56 |
| | | 1500 | | | | 14 | 24 | | | 24,63 | 29,80 |
| | | 1600 | | | | 14 | 26 | | | 25,00 | 30,25 |
| | | 1600 | | | | 20 | 33 | | | 29,00 | 35,09 |
| | | 1600 | | | | 23 | 35 | | | 32,13 | 38,87 |
| | | 1800 | | | | 15 | 29 | | | 26,63 | 32,22 |
| | | 2000 | | | | 16 | 28 | | | 28,00 | 33,88 |

| | | | | | | | | | | | |
|--------------|----|------|----|-----|-----|----|----|----|----|-------|-------|
| Ovčí pletivo | Zn | 1000 | 30 | 2,8 | 2.0 | 9 | 19 | 50 | bm | 22,63 | 27,38 |
| | | 1200 | | | | 10 | 21 | | | 24,00 | 29,04 |

| | | | | | | | | | | |
|---------------------------------------------------------------------------------------------------------------|------------------|------|------|-----|----|----|----|----|-------|-------|
| Svařované pletivo BENITA  | pozinkované (Zn) | 1200 | 6,25 | 1,8 | 11 | 30 | 50 | bm | 54,25 | 65,64 |
| | | 1500 | | | 14 | 38 | | | 64,50 | 78,05 |
| | | 1800 | | | 18 | 47 | | | 72,50 | 87,73 |

| | | | | | | | | | | |
|-------------------|-----------------|----------------------------------|--|--|--|---|---|----|-------|--------|
| Skoby lesnické Zn | Zn (250 ks/1kg) | délka 31 mm, průměr drátu 3,1 mm | | | | 1 | 1 | kg | 91,00 | 110,11 |
|-------------------|-----------------|----------------------------------|--|--|--|---|---|----|-------|--------|

| | | | | | | | | | |
|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|------|---------|---------|---|----|--------|----------|----------|
| Sloupky OPI tvarované (Zn) 50x30 mm Zatluokač sloupků | ocelový plech s povrch. úpravou Magnelis® síla stěny sloupku: 1,5 mm slouží k pohodlnému zatluokání sloupků 50x30 mm | 1600 | 11 háč. | 2,0 | 1 | ks | 159,38 | 192,84 | |
| | | 1900 | | 17 háč. | | | 2,4 | 181,25 | 219,31 |
| | | 2200 | | 2,8 | | | 203,13 | 245,78 | |
| | | | | | | | 2,5 | 1 177,50 | 1 424,78 |

LESNICKÉ PLETIVO - role po 50 m
ECONOMY: Zn - ø drátu 1,6/2,0 mm
EXCLUSIVE: Zn - ø drátu 2,0/2,5 mm

